
SK-AL-24/60

Drainage channel with 2 fixing clamps

ADVANTAGES

- Good water draining capacity that improves the functioning of the green roof
- It makes a low profile layer build-up possible
- Simple installation



DIADEM® BUILD-UP

- -extensive vegetation
- -extensive substrate (SEM)

-SK-AL-24/60 drainage channel

(may be covered with a piece of filter geotextile)

- -VLU-300 mechanical protection geotextile
- -root-resistant water proofing
- -further build-up



APPLICATION

One layered green roofs - it improves the drainage capacity where there is no dedicated drainage layer.

SPECIFICATION

Drainage channel made of aluminium for appropriate channeling of green roofs with single-course construction or of terraces and other surfaces without drainage boards; with a pre-cut drain pipe opening with a diameter of 52 mm; dimensions: 200x12.45x2.41 cm (LxWxH); weight: 0.94 kg/piece; 0.47 kg/lm.

Product: DIADEM® SK-AL-24/60 Manufacturer's certificate: APP Kft. Website: www.diadem.com







TECHNICAL DATA	
Length (cm)	200
Nominal width (cm)	6
Total width (cm)	12,45
Height (cm)	2,41
Water drainage openings (mm)	50x3
Water drainage openings (cm²/lm)	97,5
Material	aluminium
Thickness of material (mm)	1,2
Weight (kg/pc)	0,94
Weight (kg/lm)	0,47



APP Dachgarten GmbH, D-85049 Ingolstadt, Jurastrasse 21 Tel.:+49 841 370 9496 • info@grundach.com • www.grundach.com DIADEM® APP Kft., H-9028 Győr, Fehérvári út 75.



